



## High pressure switches

### IDENTIFICATION

- ▶ High pressure switch
- ▶ 90° outlet connector
- ▶ G 1/4" plain fitting for connection to process
- ▶ Degreased for use with oxygen
- ▶ Maximum working pressure: 350 bar
- ▶ Pressure reduction preset P= 25 bar / 11 bar
- ▶ Working temperature range: -20°C ÷ +80°C
- ▶ Microprocessor control system



CODE	DESCRIPTION	GAS CONNECTION	NOMINAL PRESSURE	CALIBRATION	PACKAGING	
					type	kg
<b>KT-2200-HWA1</b>	HP pressure switch for oxygen use	G 1/4" BSP	220 bar	20 bar	bag	0.07
<b>KT-2200-HWB2</b>	HP pressure switch for oxygen use	G 1/4" BSP	220 bar	11 bar	bag	0.07

## Pressure transducers

### IDENTIFICATION

- ▶ Pressure transducer with 4-20 mA output signal
- ▶ 90° outlet connector
- ▶ G 1/4" plain fitting for connection to process
- ▶ Degreased for use with oxygen
- ▶ Alarm threshold settable from alarm module AQ-2521-0001 or AQ-252B-0001
- ▶ Working temperature range: -30°C ÷ +100°C



CODE	DESCRIPTION	SCALE	GAS CONNECTION	PACKAGING	
				type	kg
<b>KT-2210-0250</b>	0-160 bar transducer for oxygen use	0 – 250 bar	G 1/4" BSP	bag	0.06
<b>KT-2210-0100</b>	0-100 bar transducer for oxygen use	0 – 100 bar		bag	0.06
<b>KT-2210-0016</b>	0-16 bar transducer for oxygen	0 – 16 bar		bag	0.06

