



LCD display alarm module - panel-mounting version

IDENTIFICATION

- ▶ Backlight blue LCD display alarm module
- ▶ Facility to interconnect multiple identical modules in master / slave configuration by means of a single twisted pair
- ▶ Availability of 16 digital inputs (ON-OFF) for minimum and maximum pressure alarms signalling and 6 inputs for valves status signalling
- ▶ Transfer of total relay-controlled alarm log (dry contact)
- ▶ Integrated protection fuse
- ▶ Visual alarms signalling by means of high luminosity flashing red LEDs
- ▶ Automatically resettable audible alarm signal
- ▶ Audible alarm mute and test buttons
- ▶ Green power-ON LED
- ▶ Alarm supervision via MODBUS-RTU protocol
- ▶ Menu-based management
- ▶ Programming with buttons or PC via RS 232 link
- ▶ Predefined alarm messages retrievable from programming menu
- ▶ Panel version for wall-embedded cabinet or for installation directly on specific rack
- ▶ Microprocessor control system



CE MARKING

Notified body: CE 0476

Risk class II B CE marking as prescribed Legislative Decree n. 46 of 24 February 1997 "Implementation of Directive 93/42/EEC concerning medical devices" and further modifications
CE marking in compliance with EMC Directive 108/2004/EC

REFERENCE STANDARD

ISO 7396-1: "Medical gas pipeline systems - Part 1: Pipeline systems for compressed medical gases and vacuum"

EN 60601-1: "Medical electrical equipment – General requirements for basic safety and essential performance"

EN 60601-1-2: "Medical electrical equipment - Electromagnetic compatibility"

EN 60601-1-8: "Alarm systems in medical electrical equipment"

* Validity of the standards is referred to the current year

- ▶ Gases: Vacuum, Oxygen, Medical Air, Nitrous Oxide, Carbon Dioxide, Instrument Air, Air for AGSS
- ▶ Storage temperature: - 20 °C ÷ +60 °C
- ▶ Working temperature: +10 °C ÷ +40 °C
- ▶ Relay 500 mA max 24 V
- ▶ Master / Slave connection via bus RS 485
- ▶ Power supply: 24 V AC - 50 Hz - 4 VA
- ▶ 1A integrated protection fuse
- ▶ Dimensions with recessed box:
(cod. **AQ-2100-0000**):
16,5 x 12 x 7,5 cm
- ▶ Subject to Directive 2012/19/UE

LCD DISPLAY ALARM - PANEL MOUNTING

CODE	DESCRIPTION	PACKAGING
AQ-2505-G001	LCD display alarm module -panel- mounting version for clinical alarms and valve status monitoring	21,5 x 13 x 11 cm 1.01 Kg

ACCESSORIES

CODE	DESCRIPTION	PACKAGING
AQ-2100-0000	Recessed box for alarm module	bag , 0.12 kg

