

IDENTIFICATION

- Probes for type 1 anaesthetic gas scavenging units (systems with blower or venturi systems)
- Facility for supply of two different hose connector sizes
- Aluminium construction with hard anodization surface treatment
- Laser-engraved production lot and product code

CE MARKING

Notified body: CE 0426 CE marking in risk class II A in accordance with Legislative Decree 24 February 1997, no. 46 "Implementation of Directive 93/42/EEC, concerning Medical Devices" and further modifications

REFERENCE STANDARD

ISO 9170-2: "Terminal units for medical gas pipeline systems - Part 2: Terminal units for anaesthetic gas scavenging systems"

ISO 7396-2: "Medical gas pipeline systems - Part 2: Anaesthetic gas scavenging disposal systems"

ISO 15001: "Anaesthetic and respiratory equipment. Compatibility with oxygen"

* Validity of the standards is referred to the current year









Terminal Units








DIMENSIONS





- Gas: Anaesthetic gas scavenging
- Storage temperature: -20 °C ÷ +60 °C
- Working temperature: +10 °C ÷ +40 °C
- Hose connector for flexible hose Øi = 22 mm or Øi = 16 mm

CODE	INTERNAL HOSE \emptyset	NOMINAL PRESSURE bar	PACKAGING		
			type	kg	pc
PF-06EP-00EV	22 mm	-15 kPa	bag	0.08	1
PF-06EP-10EV	16 mm	-15 kPa	bag	0.08	1